



US009410519B2

(12) **United States Patent**
Usui et al.

(10) **Patent No.:** **US 9,410,519 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **HIGH-PRESSURE FUEL PUMP ASSEMBLY MECHANISM**

(75) Inventors: **Satoshi Usui**, Hitachinaka (JP); **Shingo Tamura**, Hitachinaka (JP); **Katsumi Miyazaki**, Hitachinaka (JP); **Hiroyuki Yamada**, Hitachinaka (JP)

(73) Assignee: **Hitachi Automotive Systems, Ltd.**, Hitachinaka-shi (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1040 days.

(21) Appl. No.: **13/125,106**

(22) PCT Filed: **Oct. 29, 2009**

(86) PCT No.: **PCT/JP2009/068617**

§ 371 (c)(1),

(2), (4) Date: **May 19, 2011**

(87) PCT Pub. No.: **WO2010/050569**

PCT Pub. Date: **May 6, 2010**

(65) **Prior Publication Data**

US 2011/0253109 A1 Oct. 20, 2011

(30) **Foreign Application Priority Data**

Oct. 30, 2008 (JP) 2008-279041

(51) **Int. Cl.**

F02M 59/44 (2006.01)

F04B 1/04 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **F02M 59/44** (2013.01); **F02M 39/02** (2013.01); **F04B 1/0408** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC F04B 9/025; F04B 9/042; F04B 35/01; F04B 39/122; F04B 39/127; F04B 53/16; F04B 1/053; F04B 1/0421; F04B 1/0439; F04B 27/0409; F04B 27/0423; F04B 27/0442;

F04B 27/053; F04B 1/0448; F04B 1/0408; F04B 1/0426; F02M 39/02; F02M 59/102; F02M 59/44; F02M 59/48; F02M 59/485

USPC 123/509, 548, 495, 499, 500, 501, 502, 123/503, 504, 508, 514; 417/273, 470
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,986,728 A * 1/1991 Fuchs F02M 59/30
123/506
5,685,519 A 11/1997 Bircann et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 10322599 A1 * 12/2004 F02M 59/102
DE 103 44 459 A1 4/2005

(Continued)

OTHER PUBLICATIONS

Japanese Office Action dated Aug. 28, 2012 (three (3) pages).

(Continued)

Primary Examiner — Stephen K Cronin

Assistant Examiner — Brian Kirby

(74) *Attorney, Agent, or Firm* — Crowell & Moring LLP

(57) **ABSTRACT**

A high-pressure fuel pump includes a pump housing formed with a recess, a cylinder combined with the pump housing to define the recess as a pressurizing chamber, a holder securing the cylinder to the pump housing, and a plunger sliding against the cylinder to pressurize fluid in the pressurizing chamber. The holder includes an outer cylindrical surface portion fitted to an attachment fitting hole of an engine block of an internal combustion engine, and a cylindrical fitting portion fitted to an outer circumference of the cylinder. The outer cylindrical surface portion and the cylindrical fitting portion are formed in a single piece resulting from machining one and the same member.

19 Claims, 12 Drawing Sheets

